



# Светильник линейный архитектурный AL-16100-2 RGB (16 pix) DC12V/12W 48шт x SMD5050/IP65

Артикул AL-16100-2 RGB (16 pix)

В наличии 2 шт.

Склад Красноярск 1 шт.

Склад Кемерово 1 шт.

## Характеристики

Производитель ..... SignImpress



**LED linear light**  
**AL-16100**

High quality aluminum shell, surface anodized in process.  
Bright light high brightness.  
Special light source, long lifespan, high luminous efficiency.  
High quality and high thermal conductive silicon gel shell.  
Excellent conductivity and high temperature coefficient.  
High white PC lens covers with light-transmission assurance.  
Private control can be achieved by DMX512 Technology.

RoHS CE ENEC

Product specification	
<b>Basic parameters</b>	<b>Optical parameters</b>
Color temperature	High color >5000K/3000K
Beam diameter	102°/90°
LED power	0.5W
LED light source	SMD5050
Beam angle	102°/90°
IPC	Highly level III
Anti glare half-angle	30°
Life span	100,000
Material	PC
Power efficiency	90%
Control Method	remote or DMX512
Beam	1:1
<b>Electrical parameters</b>	<b>Structural parameters</b>
Material	Aluminum
Material	Aluminum
Beam diameter	25mm
Beam angle	102°/90°
Control Method	remote or DMX512
Control Mode	DMX
Control Type	DMX

Note: Refer to the data sheet for more information. Please read the manual carefully.

**DIMENSION**

**LIGHT DISTRIBUTION CURVE**

**INSTALLATION METHOD**

1. 安装方式 1: install mounting bracket

2. 安装方式 2: install light fixture