



# Светильник линейный архитектурный AL-16100-2 RGB (16 pix) DC12V/12W 48шт x SMD5050/IP65

Артикул AL-16100-2 RGB (16 pix)

В наличии 2 шт.

Склад Красноярск 1 шт.

Склад Кемерово 1 шт.

### Характеристики

Производитель ..... SignImpress



**LED linear light**  
**AL-16100** RoHS CE ENEC

- High quality aluminum shell, surface anodized in process.
- High light for high height.
- Special light source, long lifespan, high luminous efficiency.
- High quality and high thermal conductive aluminum shell with excellent conductivity and high temperature coefficient.
- High white PC lens covers with light-transmission assurance.
- Private control can be achieved by DMX512 Technology.

Product specification	
<b>Basic parameters</b>	<b>Optical parameters</b>
Color temperature	High color: 5000K/6000K
Beam diameter	102°/10°
Led source	30-30
Led light source	3030 SMD
Beam angle	102°/10°
IPC	Highly Beam III
Anti glare half-angle	30°
Life span	100,000
Material	PC
Power Voltage	12VDC
Control Method	remote control / DMX512/RF
Beam	1:14
<b>Electrical parameters</b>	<b>Structural parameters</b>
Material	Aluminum
Material	Aluminum
Beam diameter	25mm
Beam angle	102°/10°
Life span	100,000
Control Method	remote control / DMX512/RF
Control type	DMX

Note: Refer to the data sheet for more information. Please read the content on related web.

**DIMENSION**

**LIGHT DISTRIBUTION CURVE**

**INSTALLATION METHOD**