



Светильник линейный архитектурный AL-16100-2 RGB (16 pix) DC12V/12W 48шт x SMD5050/IP65

Артикул AL-16100-2 RGB (16 pix)

В наличии 2 шт.

Склад Красноярск 1 шт.

Склад Кемерово 1 шт.

Характеристики

Производитель SignImpress



LED linear light
AL-16100

High quality aluminum shell, surface anodized in process.
Bright light high brightness.
Special light source, long lifespan, high luminous efficiency.
High quality and high thermal conductive aluminum shell with excellent conductivity and high temperature coefficient.
High white PC lens covers with light-transmission assurance.
Private control can be achieved by DMX512 Technology.

RoHS CE ENEC

Product specification	
Basic parameters	Optical parameters
Color temperature	High color >5000K/3000K
Beam diameter	120°/90°
LED power	0.5W
LED light source	SMD5050
Beam angle	120°/90°
IPC	Highly level III
Anti glare half-angle	30°
Life span	100,000
Material	PC
Power efficiency	80-90%
Control Method	remote or DMX512
Beam	1:1
Electrical parameters	Structural parameters
Material	Aluminum
Material	Aluminum
Beam diameter	25mm
Beam angle	120°
Control Method	DMX512
Control type	DMX

Note: Refer to the data sheet for more information. Please read the manual or technical data.

DIMENSION

LIGHT DISTRIBUTION CURVE

INSTALLATION METHOD

1. 安装方式 1: install mounting bracket

2. 安装方式 2: install light fixture